



CCP ENTERPRISES

FLOCCULATOR

Feature :

- low maintenance cost
- low operating cost
- **MOC : SS304 & SS316**
- **available in rectangle and cylindrical shapes**
- precise control of the poly dilution process
- reduce wastage of polyelectrolyte.
- ease and comfortable in operation
- minimum operation interference
- precise control of the poly dilution process

| Model | Capacity m ³ /hr. |
|---------|------------------------------|
| FLCR25 | 25 |
| FLCR70 | 70 |
| FLCR100 | 100 |
| FLCR150 | 150 |

| | |
|----------|------|
| FLCR200 | 200 |
| FLCR300 | 300 |
| FLCR500 | 500 |
| FLCR800 | 800 |
| FLCR1200 | 1200 |

To get good performance from sludge dewatering machine the sludge has to be conditioned with suitable polyelectrolyte/ flocculant by **using technology of bottom inlet and top outlet** it has been found that a slow agitation tank with a residence

time up to 3 to 4 minutes is normally sufficient to do a good job of flocculation after the mixing of sludge and polyelectrolyte strong large size flocks will be obtained which are fed to the dewatering machine available size from 20 lit to 1500 lit.



CCP ENTERPRISES

404 sentosa pearl Waked Pune 411057

Email: ccp.enterprises1@gmail.com

pravin1747@gmail.com

Mob: +91 808731759